



Kenai

Rugged Tablet Computer

KEY FEATURES

Easy-to-use recharging function for the Trimble Kenai tablet computer

Drop-in docking connects device to charger with a simple click

Connections through Ethernet, HDMI, or USB cables to allow secure physical synchronization of collected field data with back office computers



TRIMBLE® KENAI® OFFICE DOCKING STATION

The Trimble Kenai Office Docking Station provides secure synchronization and easy charging

The Kenai Office Docking Station provides an easy way to ensure the Kenai tablet computer is automatically recharged and ready for each work day. Your workflow can utilize either Ethernet, HDMI or USB communication.

Featuring a fast and highly secure physical Ethernet connection, the Office Docking Station allows mobile workers to quickly synchronize field data with central office data servers. This capability is particularly useful in industries such as utilities, agriculture, materials handling and field service where large data sets are common. In addition to an Ethernet mode, the Office Docking Station supports HDMI, a USB client mode and DC power input.

Device Compatibility

The Kenai Office Docking station is compatible with all models of the Kenai tablet.

TECHNICAL SPECIFICATIONS

HARDWARE

- Compatible with all Trimble Kenia Tablet Computers
- Designed for desk top use with tablet tilted to enhance display readability.
- Tablet I/O, keypad and indicators accessible while docked
- Increased connectivity with USB, HDMI and Ethernet ports
- Kensington Lock
- Quickly and easily dock and connect to office equipment and network

APPROXIMATE CHARGE TIME

- 3 hours for the Kenai with Standard Battery
- 6 hours for the Kenai with Extended Battery

I/O PORTS (Front)

- USB 2.0 host

I/O PORTS (Rear)

- 2x USB 2.0 host
- RJ45 / Ethernet
- HDMI
- Audio - 3.5mm Stereo out
- DC Power

INDICATORS

Power indicator LED when Tablet is docked.

DATA SYNC

Supports ethernet connections

ENVIRONMENTAL

Operating Temperature0°C to +45° C
(32° F to 110° F)

Storage Temperature -40°C to +70°C
(-40° F to 155°F)

Humidity.....95% Non-condensing

MECHANICAL

Weight (without Tablet)1.5kg

Dimensions (h x w x d)... 60mm x 300mm x 150mm
(12" x 6" x 2.5")

Mounting.....Desk-top

Robust connector and docking pins..... Supports
5000 insertions / removals

CERTIFICATIONS

CE, FCC, CAN/CSA C22.2 No. 60950, C-U, RoHS, WEEE/REACH, C-Tick

SUPPLIED ACCESSORIES

- International AC Power adaptor



YOUR AUTHORIZED TRIMBLE DISTRIBUTION PARTNER

Trimble Navigation Limited
P.O. Box 947
Corvallis, OR 97339
541-750-9200
handhelds@trimble.com
www.trimble.com/mobile

PN 106516
Rev. A 12/15/15



www.trimble.com/mobile